

ZN30703A — Ka-Band Pyramidal Horn Transmit Antenna

PRODUCT DATASHEET | 26.5–40 GHz | ZHINAN

26.5–40 GHz	FBP320 flange	VSWR ≤1.3
-------------	---------------	-----------

1. Product Overview

The ZN30703A is a broadband pyramidal horn antenna for transmit and receive measurements. Its low VSWR, lightweight construction and defined waveguide interface support repeatable millimeter-wave EMC and RF measurement setups.

2. Technical Specifications

Parameter	Specification
Frequency range	26.5–40 GHz
Nominal impedance	50 Ω
Waveguide flange	FBP320
VSWR	≤1.3
Gain	Refer to measured performance curve
Antenna factor	Refer to measured performance curve
3 dB beamwidth	Refer to measured performance curve
Front-to-back ratio	>25 dB
Polarization isolation	>25 dB
Maximum input power	50 W
Polarization	Horizontal / vertical
Weight	Approx. 0.15 kg


3. Typical Applications

- Millimeter-wave radiated emissions and immunity measurements
- Antenna-factor and field-strength measurement chains
- Broadband transmit and receive measurements


4. Standard Package

Item	Quantity / description
Antenna	1
ZN33113 antenna stand and adapter	Optional
Flexible waveguide, 1 m	Optional
User manual and certificate	1 set


5. Antenna Gain



6. Antenna Factor



7. 3 dB Beamwidth



8. Product Image



Performance curves are reproduced from the original Chinese technical record. No measured points have been interpolated or replaced.