

ZN30706A — Millimeter-Wave Pyramidal Horn Measurement Antenna

PRODUCT DATASHEET | 50–70 GHz | ZHINAN

50–70 GHz	UG385/U flange	VSWR ≤ 1.25
-----------	----------------	------------------

1. Product Overview

The ZN30706A is a broadband pyramidal horn antenna for transmit and receive measurements. Its low VSWR, lightweight construction and defined waveguide interface support repeatable millimeter-wave EMC and RF measurement setups.

2. Technical Specifications

Parameter	Specification
Frequency range	50–70 GHz
Nominal impedance	50 Ω
Waveguide flange	UG385/U
VSWR	≤ 1.25
Gain	Refer to measured performance curve
Antenna factor	Refer to measured performance curve
3 dB beamwidth	Refer to measured performance curve
Front-to-back ratio	>25 dB
Polarization isolation	>25 dB
Maximum input power	20 W
Polarization	Horizontal / vertical
Weight	Approx. 104 g


3. Typical Applications

- Millimeter-wave radiated emissions and immunity measurements
- Antenna-factor and field-strength measurement chains
- Broadband transmit and receive measurements


4. Standard Package

Item	Quantity / description
Antenna	1
Antenna connector	Optional
Rigid waveguide, 0.5 m, dual UG385/U	Optional
1.85 mm male-to-male cable, 0.2 m	Optional
UG385/U-to-1.85 mm adapter	2, optional
ZN33104 antenna stand	Optional
User manual and certificate	1 set

5. Antenna Gain




6. Antenna Factor




Horizontal axis: frequency (GHz). Antenna factor (dB/m)

7. 3 dB Beamwidth



Horizontal axis: frequency (GHz). Beamwidth (degrees); solid: E-plane, dashed: H-plane

8. Sidelobe Level



Horizontal axis: frequency (GHz). Sidelobe level (dB); solid: E-plane, dashed: H-plane

9. Product Image



Performance curves are reproduced from the original Chinese technical record. No measured points have been interpolated or replaced.